



PHASE DIAGRAM				
PHASE 1	PHASE 2	PHASE 3	CYCLE PHASE	PED PHASE
GREEN: 25 RED: 5	GREEN: 25 RED: 5	GREEN: 15 RED: 5	GREEN: 5 RED: 5	GREEN: 7 BLACKOUT: 3 RED: 3

DO NOT SCALE FROM THIS DRAWING
All dimensions to be verified on site

- NOTES**
- All signs as per chapter 8. Distances between cones on a 30mph carriageway to be 5m minimum 9m maximum unless otherwise noted.
 - All works / traffic management shall be in accordance with the traffic signs manual chapter 8, Safety at street works and road works a code of practice 2013, Traffic Signs Regulations and General Directions.
 - Minimum no. hazard lamps: 9 per 6m hazard width.
 - Distances between signs NOT to scale for purpose of clarity.
 - Minimum sign size 750mm.
 - Absolute Minimum 3.0m running lane width to be maintained.

LEGEND

- WORKS AREA
- ASPECT OF SIGN VISION
- TRAFFIC CONES
- BARRIER
- X 5
- X 1
- X 5
- X 1
- X 1
- X 5
- X 1
- X 3
- X 5
- X 3
- X 1
- X 3
- X 1
- 3 x RAMPS
- 2 x PORTABLE CYCLE HEAD
- 6 x PORTABLE SIGNAL HEAD
- 8 x PORTABLE PEDESTRIAN SIGNAL HEAD

ROAD SPEED LIMIT

PAPER SIZE **A3**

DRAWING NUMBER

PRODUCED ON BEHALF OF **metro** traffic services ltd

metro Unit N6 Lympe Ind Est, Kent CT21 4LR
t: 01303 265700

DRAWN BY JMK | DRAWN DATE 01/03/24

DRAWING TITLE **MTS-DULWICH VILLAGE-SE21-TM-004**
DULWICH VILLAGE, LONDON SE21, TRAFFIC MANAGEMENT

REVISION No. 003 | REVISION DATE 27-05-24

COMMENTS TIMING MATRIX & PEDESTRIAN ROUTE ADDED

REVISED BY JMK | APPROVED BY JS