



PHASE DIAGRAM			
PHASE 1	PHASE 2	CYCLE PHASE	PED PHASE
GREEN: 35 RED: 10	GREEN: 20 RED: 10	GREEN: 10 RED: 10	GREEN: 7 BLACKOUT: 3 RED: 5

**DO NOT SCALE FROM THIS DRAWING**  
All dimensions to be verified on site

- NOTES**
- All signs as per chapter 8. Distances between cones on a 30mph carriageway to be 5m minimum 9m maximum unless otherwise noted.
  - All works / traffic management shall be in accordance with the traffic signs manual chapter 8, Safety at street works and road works a code of practice 2013, Traffic Signs Regulations and General Directions.
  - Minimum no. hazard lamps: 9 per 6m hazard width.
  - Distances between signs NOT to scale for purpose of clarity.
  - Minimum sign size 750mm.
  - Absolute Minimum 3.0m running lane width to be maintained.

- LEGEND**
- WORKS AREA
  - TRAFFIC CONES
  - ASPECT OF SIGN VISION
  - BARRIER
  - X 5
  - X 3
  - X 5
  - X 1
  - X 2
  - X 5
  - X 3
  - X 3
  - X 5
  - X 2
  - X 3
  - X 3
  - 5 x RAMPs
  - 1 x PORTABLE CYCLE HEAD
  - 6 x PORTABLE SIGNAL HEAD
  - 8 x PORTABLE PEDESTRIAN SIGNAL HEAD

ROAD SPEED LIMIT

PAPER SIZE **A3**

DRAWING NUMBER

PRODUCED ON BEHALF OF **metro** traffic services ltd

**metro** Unit N6 Lypmpe Ind Est, Kent CT21 4LR  
traffic services ltd t: 01303 265700

DRAWN BY JMK DRAWN DATE 23/02/24

DRAWING TITLE **MTS-DULWICH VILLAGE-SE21-TM-005**  
**DULWICH VILLAGE, LONDON SE21, TRAFFIC MANAGEMENT**

REVISION No. 004 REVISION DATE 27-05-24

COMMENTS TIMING MATRIX & PEDESTRIAN ROUTE ADDED

REVISED BY JMK APPROVED BY JS